

د افغانستان اسلامي امارت

د امارتی شرکتونو لوی ریاست
د افغان تیلی کام مخابراتی امارتی شرکت لوی ریاست
د مالی او اداری معاونیت
د تدارکاتو ریاست
د پیرو دلو آمریت
د تخنیکي او اجناسو پیرو دلو مدیریت

(موضوع: تهیه و تدارک تجهیزات تخنیکي جهت ارایه خدمات FTTH به مشترکین شرکت مخابراتی افغان تیلی کام ولایت کابل)

{1125}

شماره درخواست نرخدهی:

{1446/3/27}

تاریخ صدور درخواست نرخدهی به قمری:

{1404/6/29}

تاریخ صدور درخواست نرخدهی به شمسی:

جنس فوق ضرورت : معاونیت عملیاتی سیمدار (مدیریت سروی FTTH)

تاریخ ترتیب استعلام : (27 / 3 / 1447)

- (1) اداره {نام اداره تدارکاتی را درج کنید} تخصیص بودجه لازم برای تدارک اجناس/ خدمات غیر مشورتی مندرج این درخواست را دارد.
- (2) آفر سربسته شما الی {تاریخ و وقت را درج کنید} یا قبل از آن به دفتر {مدیریت خریداری امریت تهیه و تدارکات شرکت افغان تیلیکام} تسلیم داده شود.
- (3) آفر ها نیکه بعد از میعاد تسلیمی ارائه گردند، بدون اینکه باز شود مسترد می گردد. پاکت حاوی آفر باید به صورت واضح عبارت نرخ برای {نام اجناس/ خدمات غیر مشورتی را درج کنید} نشانی شده باشد.
- (4) آفر ارائه شده در آفرها باید الی مدت (30) روز تقویمی سر از تاریخ ختم میعاد تسلیمی آفرها اعتبار داشته باشد.
- (5) در صورت تغییر در مقدار نیازمندی، اداره می تواند مقدار نیازمندی تقاضا شده را الی (25) فیصد زیاد و یا کم نماید، مشروط به اینکه قیمت مجموعی آن از حدود صلاحیت پولی برای درخواست نرخ گیری تجاوز ننماید.
- (6) ترجیح داخلی مطابق حکم چهارم طرز العمل تدارکات قابل اجرا است. {مورد ترجیح داخلی و فیصدی آنرا درج نمائید}.
- (7) آفر گشائی در محضر عام حتمی نبوده و فرمایش دهنده مکلف به قبول نازلترین نرخ نمی باشد. در صورت رد هر یک یا تمام آفرها فرمایش دهنده کدام مسئولیت در قبال داوطلب تهیه/ارائه کننده ندارد.
- (8) آفر دهنده اسناد ذیل را با آفر خویش ضمیمه می نماید:
 - 1- جواز تجارتي/ فعالیت/ کار قابل اعتبار؛
 - 2- نمبر تشخیصیه مالیه؛
 - 3- اجازه نامه تولید کننده (در صورت لزوم).
 - 4-
- (9) سند نرخ گیری تکمیل و توسط شخص با صلاحیت یا نماینده تهیه/ ارائه کننده در هر صفحه مهر امضاء شده باشد.
نام کارمند صادر کننده درخواست نرخ گیری:

امضاء هیت

امضاء هیت

امضاء هیت

جدول اقلام و قیمت ها

شماره	اسم و تشریح با مشخصات تخنیکی اقلام	واحد	مقدار	قیمت فی واحد به افغانی	قیمت مجموعی به افغانی
1	Rack mounted ODF 144 core FTTH Rack Mount ODF 144 Cores 4U Fiber Optic Odf 144 Port Optical Distribution Frame Odf full loaded With Sc Apc Adapter Pigtail Type: Fiber optic patch panel Color: Black Dimensions:4 U Main Components: Splice Tray, Pigtail Adapter, Fiber clips, etc. Model Number: 144 ports patch panel Warranty Time: 5 YEARS Product name: 144 ports patch panel Connector: SC/APC Material:Metal Thickness: 0.8/1.0mm Type: Racks& Enclosure Single package size: 53.5X32X30 cm Rack size: 19 inch 4 U No of splicing tray: 6 trays	PCS	100		
2	SC/APC fast connector SC/APC Type fiber optic connector FTTH fiber optical Simplex SC/APC quick fiber optic fast connector Original and Brand Connector with less than 0.2 dBm loss Connector type: SC/APC; Mode: Single mode (9/125) Length: 60mm; Tensile Strength: >30N Fiber mode: Single mode Operation time: About 50s (no fiber cut) Insertion loss: <0.2dB; Return Loss: >55dB compatible with 2.0x3.0mm and 1.6x2.0mm FTTH butterfly cables High durability and reusability up to 100+ times.	PCS	20000		
3	SC/UPC Fast Connector SC/UPC Type fiber optic connector FTTH fiber optical Simplex SC/UPC quick fiber optic fast connector Original and Brand Connector with less than 0.2 dBm loss Connector type: SC/UPC; Mode Length: 60mm; Tensile Strength: >30N Fiber mode: Single mode Operation time: About 50s (no fiber cut) Insertion loss: <0.2dB; Return Loss: >55dB compatible with 2.0x3.0mm and 1.6x2.0mm FTTH butterfly cables High durability and reusability up to 100+ times. Model No: UT-SC6001 Connector type: SC/UPC Length: 60mm Fiber mode: Single mode Operation time: About 50s (no fiber cut) Insertion loss: <0.3dB Insertion loss: 0.2dB Return loss: >55 dB UPC	PCS	20000		
4	144 core Fiber Joint enclosure 144 Core Optic Splice Joint Closure 2 in 2 out Horizontal Types F002 are used to distribute, splice, and store the outdoor optical cables which enter and exit from the ends of the closure. Dimensions A B C(mm): 645*220*175 Max Capacity:Splice 144 Fibers (6 trays,24 core/tray) Number of Cable Entrance/Exit:2 in 2 out Diameter of Cable:p 40mm Material: ABS Weight: 5.75 kg Standard Accessories 144 Core Optic Splice Joint Closure 2 in 2 out Horizontal Types: Metal spanner: 1pcs Metal hanger: 8pcs Sealing rubber strip: 2pcs Insulating tape: 1pcs Metal ring 4pcs Plastic ring: 16pcs Plastic plug: 4pcs Heat-shrink sleeve:1.2mm*60mm 96pcs Plastic Cable Tie	PCS	200		
5	96 core Fiber Joint closure 96 Core Optic Splice Joint Closure 3 in 3 out Horizontal Types F003 are used to distribute, splice, and store the outdoor optical cables which enter and exit from the ends of the closure. Material: ABS Dimensions A*B*C(mm): 445*220*110 Max Capacity:Splice 96 Fibers (4 trays,24 core/tray) Number of Cable Entrance/Exit: 3 in 3 out Diameter of Cable:p 11mm,p 16mm, 23mm Weight: 2.15 kg Standard Accessories: Metal spanner: 1pcs Metal hanger: 2pcs Sealing rubber strip: 1pcs Insulating tape: 1pcs Plastic ring: 6pcs Plastic plug: 6pcs Rubber waterproof strip: 2pcs Cable tie:3mm 110mm 8pcs Heat-shrink sleeve:1.2mm*60mm 96pcs	PCS	300		
6	72 core Fiber Joint enclosure 72 Core Optic Splice Joint Closure 3 in 3 out Horizontal Types F003 are used to distribute, splice, and store the outdoor optical cables which enter and exit from the ends of the closure. Dimensions A B°C(mm): 445*220*110 Max Capacity:Splice 72 Fibers (3 trays, 24 core/tray) Number of Cable Entrance/Exit: 3 in 3 out Material:ABS Diameter of Cable:p 11mm, 16mm, 23mm Standard Accessories: Metal spanner: 1pcs Metal hanger: 2pcs Sealing rubber strip: 1pcs Insulating tape: 1pcs Plastic ring: 6pcs Plastic plug: 6pcs Rubber waterproof strip: 2pcs Cable tie:3mm*110mm 8pcs Heat-shrink sleeve:1.2mm*60mm 72pcs	PCS	300		
7	48 core Fiber joint enclosure 3port in 3port out Installation kit; Sealing kit; Splice Sleeves; 12fibers per cassette; The splice closure shall be suitable for the installation in manhole/Handhold; The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc; The splice closure shall have mechanical strength to withstand tensile, compressive bending and torsion stresses expected in normal condition; The splice closure shall be applied for both-splicing types between optical fibre cables and optical fiber cable and termination optical fiber cable; The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc; • with all required accessories. Material of housing: High-strength PP+GF Material of internal components: High-strength ABS Material of metal accessory: High-quality stainless steel	PCS	300		

				External dimension(mm): 32*135*67 Color: Black Number of ports: 4 Sealing type: Mechanical Fiber cable diameter of 2 small ports (mm): 08~013 Fiber cable diameter of 2 middle ports (mm): 08~017 Fiber cable diameter of 2 big ports (mm): 08~020 IP grade: IP68 Capacity (Max): 4x12=48 Splice tray type and quantity can be optional as customer's request	
		300	PCS	24 core Fiber joint closure Product Name: 3port in 3 port out 24 Core Fiber Optic Splice Joint Closure Horizontal Model NO: Splice Closure Material:ABS Condition: New Capacity: 24 Cores Color: Black with splicing trays, each splicing tray should support 24 fiber cores, and a large- sized splicing tray should be used to easily accommodate all 24 fibers; Installation kit; Sealing kit; *Splice Sleeves; 12 fibers per cassette; The splice closure shall be suitable for the installation in manhole/Handhold; The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc; The splice closure shall have mechanical strength to withstand tensile, compressive bending and torsion stresses expected in normal condition; The splice closure shall be applied for both-splicing types between optical fiber cables and optical fiber cable and termination optical fiber cable; The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc; with all required accessories. Dimension: 480 160*105mm	8
		300	PCS	SC/UPC – SC/APC Patch Cord • 100% tested • Model Number: SC/UPC SC/APC Patch Cord • Jacket: LSZH Connector: SC/UPC SC/APC • Fiber Cores: G657A1 • Maximum Connector Loss: 0.50 dB Typical Connector Loss: 0.30 dB • Typical Return Loss: -55 dB • Fiber length: 5 meter • Fiber diameter: 2mm • Feature: Simplex Original and Best quality from a brand company	9

نوت: جنس مذکور 100% مطابق مشخصات ذکر شده باشد، در غیر آن قابل قبول نبوده و مسترد میگردد.

✓ په هره تدارکاتی پروسه کی چی یو شرکت د اړونده نرخ اخیستنې استعمال مطابق د اجناسو، خدماتو او ساختمانی چارو د تهیه او ترسره کولو لپاره ګټونکی وبلل شی او قیمت یی له (100000) سل زره افغانیو څخه لوړ وی مخکی له دی چی د برنده کی اطلاعیه ترلاسه کړی باید له مجموعی قیمت څخه 10% لس فیصده د تضمین په ډول د افغان ټیلی کام مخابراتی امارتی شرکت بانکی حساب ته جمع او اصلی اویز یی د مالی محترم ریاست له تصدیق څخه وروسته د تهیه او تدارکاتو ریاست پیروډلو آمریت ته تسلیم کړی.

✓ که چیرته کوم ګټونکی شرکت دلس فیصده تضمین له ورکولو څخه انکار وکړی شرکت به یی د افغان ټیلی کام مخابراتی امارتی شرکت په تورلیست کی ثبت کپړی او د یوګال لپاره به د افغان ټیلی کام مخابراتی امارتی شرکت دخوش خرید له لاری په تدارکاتی پروسوکی ګډون نه شی کولای.

✓ که چیرته د ګټونکی شرکت لخوا غوښتل شوی اجناس/خدمات په وخت سره تهیه او اماده نه شی یعنی شرکت ونه توانیږی چی اجناس/خدمات/ساختمانی چاری تهیه او ترسره کړی دنه تهیه کولو په صورت کی به د شرکت تضمین دیوګال په پار افغان ټیلی کام مخابراتی امارتی شرکت سره پاتی وی او شرکت به یی په تورلیست کی شاملیږی یوګال وروسته به یی بیرته تضمین شرکت ته سپارل کپړی.

✓ پورته ذکرشوی پریکړی د شاروالی جواز لرونکو لپاره د تطبیق وړ نه دی.

مجموع قیمت به ارقام بشمول مالیات : عدد

مجموع قیمت به حروف بشمول مالیات:

مجموع مبلغ مالیات به ارقام و حروف:

مجموع قیمت به ارقام بدون مالیات: عدد (قابل پرداخت)

مجموع قیمت به حروف بدون مالیات (قابل پرداخت)

مدت ضمانت (ورانتی/ گرنټی) بعد از تاریخ اكمال:

مشخصات ضم پیشنهاد می باشد:

مشخصات تخنیکي اجناس

شماره	اقلام	مشخصات
آدرس مشخص شرکت: ایمیل آدرس شرکت:		
اسم تهیه/ ارائه کننده:	مهر تهیه/ ارائه کننده	
اسم شخص یا نماینده با صلاحیت تهیه/ ارائه کننده:		
امضای شخص یا نماینده تهیه/ ارائه کننده:		
تاریخ:		
شماره تلفون حتمی:		

یادداشت: فرمایش گیرنده کاپی رهنمود، ساخت و مدل، بروشور و یا فهرست تجهیزات یا خدماتی را که اكمال می نماید ضمیمه نماید. معلومات فوق جهت ارزیابی مؤثر آفرها استفاده می گردد.

شرایط تدارک و پرداخت

شرایط ذیل صرف با موافقه تحریری فرمایش دهنده قابل تغییر می باشد.

- (1) تهیه کننده مکلف به پرداخت تأمینات و تضمینات می باشد، تأمینات از سر جمع پول 5 الی 15 فیصد اخذ میگردد و بعد از تکمیل و رانتهی به اکانت شرکت انتقال میگردد.
- (2) بعد از اكمال خدمات غیر مشورتی/ تهیه اجناس، تهیه/ ارائه کننده باید نسخه اصلی و (2) کاپی بل (Invoice) را به فرمایش دهنده تسلیم نماید؛
- (3) پرداخت توسط فرمایش دهنده، طی مدت (30) روز کاری درمقابل مقدار واقعی اجناس/خدمات غیر مشورتی تهیه شده صورت می گیرد.
- (4) فرمایش دهنده میتواند در حالات ذیل با ارسال اطلاعیه کتبی به تهیه/ ارائه کننده، امر خریداری را کاملاً یا قسماً فسخ نماید:
 - 1- تهیه/ ارائه کننده موفق به تحویل بخش یا تمام اجناس در ظرف مدت معینه در امر خریداری نشود؛
 - 2- تهیه/ ارائه کننده موفق به اجرای مکلفیت های دیگر تحت امر خریداری نشود.
 - 3- هرگاه در اجناس اكمال شده یا خدمات ارائه شده نواقص و یا کاستی ها مشاهده گردد، تهیه/ ارائه کننده مکلف به رفع نواقص و کاستی ها در مدت (3) روز کاری بعد از دریافت اطلاعیه در مورد می باشد، در غیر آن فرمایش دهنده می تواند امر خریداری را فسخ نماید.
 - 4- هرگاه تهیه/ ارائه کننده، در جریان داوطلبی و یا حین اجرای وظایف محوله تحت امر خریداری اقدام به فساد و تقلب نموده باشد.
 - (5) هرگاه در درخواست نرخ گیری میعاد ضمانت (وارنتی/ گرننتی) تصریح گردیده باشد، تهیه/ ارائه کننده مکلف به تعویض در طول مدت معینه می باشد.

اصلاح اشتباهات محاسبوی

(1) اشتباهات محاسبوی طور ذیل تصحیح می گردد:

- 1- در صورت تفاوت میان مبلغ به ارقام و حروف، مبلغ به حروف قابل اعتبار می باشد؛
- 2- در صورتیکه تفاوت میان قیمت فی واحد و قیمت مجموعی وجود داشته باشد، قیمت فی واحد برای ارزیابی قیمت ها و ترتیب امر خریداری قابل اعتبار می باشد؛
- 3- در صورت موجودیت تفاوت میان نرخ فی واحد و قیمت مجموعی (حاصل ضرب مقدار در نرخ فی واحد)، نرخ فی واحد قابل اعتبار می باشد، هرگاه از نظر فرمایش دهنده اشتباه در نقاط اعشاری در قیمت فی واحد برجسته باشد، در این صورت قیمت مجموعی اقلام طوریکه نرخ داده شده است قابل اعتبار بوده و قیمت فی واحد باید اصلاح شود.
- 4- فرمایش دهنده مطابق مندرجات فوق اشتباهات محاسبوی را اصلاح و بعد از اخذ موافقه کتبی داوطلب در قیمت مجموعی آفر محاسبه می نماید.
- 5- داوطلب مکلف به پذیرش اشتباهات محاسبوی در آفر خویش می باشد. در صورت عدم پذیرش اشتباهات محاسبوی توسط داوطلب، آفر وی رد می گردد.

نوت:

