

کی جیتاں ہجرت

## A collection of various electronic equipment and accessories. On the left, there are several handheld devices, some with screens displaying data. In the center and right, there are various cables, connectors, and a black carrying bag. The items are arranged in a somewhat organized manner, suggesting they are part of a kit or inventory.

مکتبہ اسلامیہ بنیاد

မကွေးပြည်နယ်



|    |                                                              |     |
|----|--------------------------------------------------------------|-----|
| 1  | معرفی شرکت افعان تیلی کام :                                  | 1   |
| 1  | پس منظر پروژه و شبکه فایبر نوری:                             | 1   |
| 2  | هدف پروژه:                                                   | 3   |
| 4  | مشخصات نیازمندی:                                             | 4   |
| 5  | مشخصات تجهیزاتی:                                             | 5   |
| 5  | Optical Distribution Frame (ODF):                            | 5.1 |
| 6  | fiber joint enclosure:                                       | 5.2 |
| 7  | Patch Cords:                                                 | 5.3 |
| 8  | Patch Cords (E2000):                                         | 5.4 |
| 9  | Fiber Cable Splicing Machine (Fujikura 90S+ Fusion Splicer): | 5.5 |
| 11 | Power Meter (EPM-50 Power Meter):                            | 5.6 |
| 11 | Light Source (ELS-50 Light Source):                          | 5.7 |
| 12 | Optical Time-Domain Reflectometer (OTDR):                    | 5.8 |
| 13 | فرم‌های فایبر نوری و فرم‌های گسترده:                         | 6   |
| 13 | اجناس:                                                       | 6.1 |
| 14 | جدول تحویل دهی:                                              | 6.2 |
| 16 | میزان قرارداد کار:                                           | 7   |
| 16 | میزان قرارداد کار:                                           | 7.1 |
| 16 | میزان قرارداد کار:                                           | 7.2 |
| 16 | میزان قرارداد کار:                                           | 7.3 |
| 16 | میزان قرارداد کار:                                           | 7.4 |
| 16 | میزان قرارداد کار:                                           | 7.5 |

محتویات:







2

| ردیف | توضیحات                                                                                                | واحد | مقدار | قیمت فی واحد به | قیمت فی واحد به حد | قیمت مجموعی به |
|------|--------------------------------------------------------------------------------------------------------|------|-------|-----------------|--------------------|----------------|
| 1    | 12 core ODF with all accessories based on SoW memorandum# 5.1 Technical Requirements                   | pcs  | 600   |                 |                    |                |
| 2    | 48 core ODF with all accessories based on SoW memorandum# 5.1 Technical Requirements                   | pcs  | 100   |                 |                    |                |
| 3    | 96 core ODF with all accessories based on SoW memorandum# 5.1 Technical Requirements                   | pcs  | 80    |                 |                    |                |
| 4    | 48 core fiber joint enclosure with all accessories based on SoW memorandum# 5.2 Technical Requirements | pcs  | 1,000 |                 |                    |                |
| 5    | 96 fiber joint enclosure with all accessories based on SoW memorandum# 5.2 Technical Requirements      | pcs  | 1,000 |                 |                    |                |
| 6    | 144 fiber joint enclosure with all accessories based on SoW memorandum# 5.2 Technical Requirements     | pcs  | 1,000 |                 |                    |                |
| 7    | SC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-0.5m based on SoW memorandum# 5.3 Technical Requirements               | pair | 500   |                 |                    |                |
| 8    | SC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-1m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 9    | SC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-2m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 10   | SC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-3m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 11   | SC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-5m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 12   | SC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-10m based on SoW memorandum# 5.3 Technical Requirements                | pair | 500   |                 |                    |                |
| 13   | SC/APC-SC/UPC-Duplex-SM-SM-Φ3.0-0.5m based on SoW memorandum# 5.3 Technical Requirements               | pair | 500   |                 |                    |                |
| 14   | SC/APC-SC/UPC-Duplex-SM-SM-Φ3.0-1m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 15   | SC/APC-SC/UPC-Duplex-SM-SM-Φ3.0-2m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 16   | SC/APC-SC/UPC-Duplex-SM-SM-Φ3.0-3m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 17   | SC/APC-SC/UPC-Duplex-SM-SM-Φ3.0-5m based on SoW memorandum# 5.3 Technical Requirements                 | pair | 500   |                 |                    |                |
| 18   | SC/APC-SC/UPC-Duplex-SM-SM-Φ3.0-10m based on SoW memorandum# 5.3 Technical Requirements                | pair | 500   |                 |                    |                |

(توضیحات: این جدول شامل تجهیزات و ملزومات زیر می باشد. قیمت ها بر اساس آخرین قیمت های اعلام شده در بازار می باشد. قیمت ها به ریال می باشد.)

4 مشخصات/ نیازمندی:







| رقم العنصر |      |       |  | الوصف                                                                                                                                                        |  |  |
|------------|------|-------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| 39         | pair | 2,000 |  | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-2m based on SoW memorandum# 5.3 Technical Requirements                                                                       |  |  |
| 40         | pair | 2,000 |  | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-3m based on SoW memorandum# 5.3 Technical Requirements                                                                       |  |  |
| 41         | pair | 2,000 |  | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-5m based on SoW memorandum# 5.3 Technical Requirements                                                                       |  |  |
| 42         | pair | 2,000 |  | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-10m based on SoW memorandum# 5.3 Technical Requirements                                                                      |  |  |
| 43         | pair | 400   |  | Singlemode 1 E2000/APC-SC/PC G.652D 20M Yellow   AE2000-SC-S2- L40//E2000/APC-SC/UPC SM SX 2.0mm PVC 20M based on SoW memorandum# 5.4 Technical Requirements |  |  |
| 44         | pair | 400   |  | Singlemode 1 E2000/APC-SC/PC G.652D 10M Yellow   AE2000-SC-S2- L40//E2000/APC-SC/UPC SM SX 2.0mm PVC10M based on SoW memorandum# 5.4 Technical Requirements  |  |  |
| 45         | pcs  | 10    |  | Splicing Machine 90st+ and tools kits with all accessories based on SoW memorandum# 5.5 Technical Requirements                                               |  |  |
| 46         | pcs  | 5     |  | Power Meter based on SoW memorandum# 5.6 Technical Requirements                                                                                              |  |  |
| 47         | pcs  | 20    |  | Light Source based on SoW memorandum# 5.7 Technical Requirements                                                                                             |  |  |
| 48         | pcs  | 5     |  | Optical Time-Domain Reflectometer (OTDR) based on SoW memorandum# 5.8 Technical Requirements                                                                 |  |  |

## 5.1 Optical Distribution Frame (ODF):

### General Description:

Note: the pigtail, adapter of ODF & all types of patch cords shall be branded products supplied by globally recognized optical fiber manufacturers, including Corning (USA), Prysmian Group (Italy), YOF (China), Fujikura Ltd. (Japan), Sumitomo Electric (Japan), Hengyong Optic-Electric (China), and Sterlite Technologies (STL) (India), from any other non-globally recognized manufacturers will not be accepted and shall be rejected. The selected manufacturer must be officially confirmed through written communication from the manufacturer's official corporate email address:

- Rack mount sliding ODF, 24 fibers per cassette, including Splice Sleeves;
- Adapter Duplex SC/SC for 48 and 96 core ODF and simplex SC/SC for 12 core ODF;
- Pigtail shall have enough length to satisfy bend radius required (ITU-T G657.A1) and fit on the ODFs supplied
- The ODF shall be equipped with cassettes, each supporting 24 fibers per cassette. The external dimensions of each cassette shall be (198 × 122 × 16) mm, with a tolerance of ±5%, in accordance with the referenced picture.
- Sleeves shall be of the type compatible with the supplied optical core cables;
- Flexible: based on below picture as mentioned rack mount ODF is relatively flexible during applications;
- Half (50%) of ODF Pigtail SC/APC & Adapter SC/APC;
- Half (50%) of ODF Pigtail SC/UPC & Adapter SC/UPC;
- with all required accessories.

### Standards Comply:

The product must be produced and tested following the standards outlined below.

- UL94: Test for flammability of plastic materials for parts in devices and appliances
- IEC61300-2: Fiber optic interconnecting devices and passive components - Basic test and measurement procedures
- IEC60068-2: Basic environmental testing procedures for electric and electronic products

### Characteristics:

- IP20, scratch resistant powder paint.
- Adjustable terminal box recess up to 50mm.
- Terminal box panel with stopper at full travel. The Maximum travel of guide rail is 200mm

### Mechanical specifications:

| Item                            | Specifications                                          | Note |
|---------------------------------|---------------------------------------------------------|------|
| Material of housing             | Coated cold-rolled steel                                |      |
| Material of internal components | Flame retardant of ABS                                  |      |
| Material of metal accessory     | High-quality stainless steel                            |      |
| Color                           | Black and cassette be white                             |      |
| Adapter & pigtail durability    | ≥1000 cycle                                             |      |
| Insulation resistance           | $\geq 2 \times 10^4 \text{ M}\Omega / 500\text{V (DC)}$ |      |
| Withstand Voltage               | $\geq 3000\text{V (DC)} / 1\text{min}$                  |      |

### Optical specifications:



| Item               | Test Method           | Specification          | Note    |
|--------------------|-----------------------|------------------------|---------|
| Insertion loss(dB) | IEC61300-3-4-Method B | Maximum ≤ 0.25dB       | Grade B |
| Return loss(dB)    | IEC61300-3-6-Method 1 | APC ≥ 60dB, UPC ≥ 50dB |         |
| Random connection  | IEC61300-3-4          | Maximum ≤ 0.3dB        |         |



Handwritten signature in blue ink.

Handwritten signature in blue ink.





## 5.2 fiber joint enclosure:

### Characteristics:

- 3 in/3 Out, Installation kit, Sealing kit, Splice Sleeves;
- The joint closure shall be equipped with cassettes, each supporting 24 fibers per cassette. The external dimensions of each cassette shall be (198 × 122 × 16) mm, with a tolerance of ±5%, in accordance with the referenced picture.
- The splice closure shall be suitable for the installation in manhole/Handhold;
- The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc;
- The splice closure shall have mechanical strength to withstand tensile, compressive bending and torsion stresses expected in normal condition;
- The splice closure shall be applied for both- splicing types between optical fibre cables and optical fibre cable and termination optical fibre cable;
- The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc;
- The splice closure shall consist of anti-corrosive materials, resistant to acids, oil and pollutants, etc;
- with all required accessories.

### Specifications:

| Item                                      | Specifications                                                                                                                                                                                                                                                                                                                      | Note                                                                              |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Material of housing                       | High-strength PP+GF                                                                                                                                                                                                                                                                                                                 |                                                                                   |
| Material of internal components           | High-strength ABS                                                                                                                                                                                                                                                                                                                   |                                                                                   |
| Material of metal accessory               | The joint closure and all related components shall be manufactured from high-quality stainless steel.<br>The cable central strength member (FRP) fixing point, including all nuts and bolts, shall be made of corrosion-resistant materials to ensure long-term durability and protection against rust and environmental conditions |                                                                                   |
| External dimension(mm) for 48 core fibers | (441*203*108) ± 5%                                                                                                                                                                                                                                                                                                                  |  |
| Weight:                                   | 2 kg± 10%                                                                                                                                                                                                                                                                                                                           |                                                                                   |
| External dimension(mm) for 96 core fibers | (445*220*110) ± 5%                                                                                                                                                                                                                                                                                                                  |  |
| Weight:                                   | 2.15 kg± 10%                                                                                                                                                                                                                                                                                                                        |                                                                                   |



*[Handwritten signature]*

*[Handwritten signature]*





| Category    | Items         | Optical Characteristics |                        |                        |
|-------------|---------------|-------------------------|------------------------|------------------------|
|             |               | Attenuation at 1310 nm  | Attenuation at 1383 nm | Attenuation at 1550 nm |
| Description | Unit          | dB/km                   | dB/km                  | dB/km                  |
|             | Before cabled | ≤ 0.34                  | ≤ 0.34                 | ≤ 0.20                 |
|             | After cabled  | ≤ 0.40                  | ≤ 0.40                 | ≤ 0.30                 |

ITU-T G657.A1

Fiber Performance:

| Connector Type | IL(dB)    | RL(dB) | Durability | Temperature Cycling |
|----------------|-----------|--------|------------|---------------------|
| LC and SC      | 0.30(Max) | ≥36    | 500 times  | ≤0.20               |


Connector Performance:

| Fiber Count | Bending Radius(mm) |         | Temperature(°C) |              | Package |
|-------------|--------------------|---------|-----------------|--------------|---------|
|             | Static             | Dynamic | Operation       | Installation |         |
| 1           | 10D                | 20D     | -20~+60         | -5~+50       | PE bag  |

Mechanical Performance:

- Patch shall have enough to satisfy bend radius required (ITU-T G657.A1) and fit on the Rack & ODFs
- Brands core patch cords;
- APC type;
- UPC type;
- Loose tube structure LSZH materials for outer sheath

### 5.3 Patch Cords:



|         |            |                                                                                    |                                                                  |                                      |                      |                            |                                                      |                                                       |                                                    |                  |                                                                                                                                                                                                             |
|---------|------------|------------------------------------------------------------------------------------|------------------------------------------------------------------|--------------------------------------|----------------------|----------------------------|------------------------------------------------------|-------------------------------------------------------|----------------------------------------------------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight: | 5.75 kg10% |  | External dimension(mm) for 144 core fibers<br>(645*220*175) ± 5% | Color<br>Black and cassette be white | Number of ports<br>6 | Sealing type<br>Mechanical | Fiber cable diameter of 2 small ports (mm)<br>Φ8~Φ16 | Fiber cable diameter of 2 middle ports (mm)<br>Φ8~Φ20 | Fiber cable diameter of 2 big ports (mm)<br>Φ8~Φ23 | IP grade<br>IP68 | Capacity (Max) per cassette for 48,96 & 144 core joint<br>1- (6cassette /joint) 6 x24(=144, 2- (4cassette /joint) 4x24=96, 3-(3cassette /joint one will be extra, it mean for 48 will be have 3 pc) 3x24=48 |
|         |            |                                                                                    |                                                                  |                                      |                      |                            |                                                      |                                                       |                                                    |                  |                                                                                                                                                                                                             |



| Geometrical Characteristics | Zero dispersion wavelength                             |           |  |
|-----------------------------|--------------------------------------------------------|-----------|--|
|                             | nm                                                     | 1312 ± 12 |  |
| Geometrical Characteristics | Zero dispersion slope                                  |           |  |
|                             | ps/(nm <sup>2</sup> ·km)                               | ≤ 0.092   |  |
| Geometrical Characteristics | Cable cut-off wavelength λ <sub>cc</sub>               |           |  |
|                             | nm                                                     | ≤ 1260    |  |
| Geometrical Characteristics | Mode field diameter (MFD) at 1310 nm                   |           |  |
|                             | μm                                                     | 8.7~9.5   |  |
| Geometrical Characteristics | Mode field diameter (MFD) at 1550 nm                   |           |  |
|                             | μm                                                     | 9.9~10.9  |  |
| Geometrical Characteristics | Group Index of Refraction (Typical) at 1310 nm         |           |  |
|                             | /                                                      | 1.466     |  |
| Geometrical Characteristics | Group Index of Refraction (Typical) at 1550 nm         |           |  |
|                             | /                                                      | 1.467     |  |
| Geometrical Characteristics | Macro-bend loss (1 turn, 16mm radius) at 1550nm        |           |  |
|                             | dB                                                     | ≤ 0.05    |  |
| Geometrical Characteristics | Macro-bend loss (100 turn, 25mm radius) at 1310&1550nm |           |  |
|                             | dB                                                     | ≤ 0.05    |  |
| Geometrical Characteristics | Macro-bend loss (100turns, 30mm radius) at 1620nm      |           |  |
|                             | dB                                                     | ≤ 0.05    |  |
| Geometrical Characteristics | Cladding diameter                                      |           |  |
|                             | μm                                                     | 125 ± 0.7 |  |
| Geometrical Characteristics | Cladding non-circularity                               |           |  |
|                             | %                                                      | ≤ 1.0     |  |
| Geometrical Characteristics | Coating diameter                                       |           |  |
|                             | μm                                                     | 245 ± 7   |  |
| Geometrical Characteristics | Coating/cladding concentricity error                   |           |  |
|                             | μm                                                     | ≤ 12.0    |  |
| Geometrical Characteristics | Coating non-circularity                                |           |  |
|                             | %                                                      | ≤ 6.0     |  |
| Geometrical Characteristics | Core/cladding concentricity error                      |           |  |
|                             | μm                                                     | ≤ 0.6     |  |



#### 5.4 Patch Cords (E2000):

- Single mode 1 /APC-SC/PC G.652D 20M Yellow | AE2000-SC-S2-L40//E2000/APC-SC/U/PC SM SX 2.0mm 20M//E2000/APC-SC/U/PC G652D 1F Φ3 PVC 20M;
- Fiber Type: ITU-T G.652D (Single mode, Low Water Peak Fiber);
- Wavelengths Supported:
  - 1310 nm
  - 1550 nm
  - Extended support: 1625 nm
- Attenuation:
  - ≤ 0.36 dB/km @ 1310 nm
  - ≤ 0.22 dB/km @ 1550 nm
  - ≤ 0.24 dB/km @ 1625 nm
- Bandwidth / Applications: Optimized for long-haul, metro, and access networks (DWDM, OTN, SDH, Ethernet, etc.);
- Insertion Loss: ≤ 0.3 dB (typical ≤ 0.2 dB);
- Cable Jacket Material: PVC / LSZH / OFNR / OFNP (as specified);
- Cable Diameter: 3.0 mm (standard);
- Color: Yellow (standard for Singlenmode);
- Operating Temperature: -40 °C to +75 °C;
- Storage Temperature: -45 °C to +85 °C.





# 5.5 Fiber Cable Splicing Machine (Fujikura 90S+ Fusion Splicer):

## TECHNICAL SPECIFICATIONS:


|    |                              |                                                                                                     |
|----|------------------------------|-----------------------------------------------------------------------------------------------------|
| 1  | Fiber Alignment Method       |                                                                                                     |
| 2  | Fiber Count Can Be Spliced   |                                                                                                     |
| 3  | Applicable Fiber             | Fiber Type<br>Single-mode optical fiber<br>Multimode optical fiber                                  |
| 4  | Applicable Coating           | Cladding Dia.<br>80 to 150 $\mu$ m<br>Coating dia.: Max. 3,000 $\mu$ m<br>Cleave length: 5 to 16 mm |
| 5  | Fiber Splice Performance     | Sheath Clamp                                                                                        |
|    |                              | Splice Loss                                                                                         |
|    |                              | ITU-T G.657: Avg. 0.02 dB                                                                           |
|    |                              | ITU-T G.655: Avg. 0.04 dB                                                                           |
|    |                              | ITU-T G.654: Avg. 0.04 dB                                                                           |
| 6  | Applicable Protection Sleeve | Splice Loss                                                                                         |
|    |                              | SM FAST mode: Avg. 8 to 10 sec.                                                                     |
|    |                              | SM AUTO mode: Avg. 11 to 13 sec.                                                                    |
|    |                              | AUTO mode: Avg. 14 to 16 sec.                                                                       |
|    |                              | Heat-shrinkable sleeve                                                                              |
| 7  | Sleeve Heat Performance      | Heat Time                                                                                           |
|    |                              | 60 mm mode: Avg. 9 to 10 sec.                                                                       |
|    |                              | 60 mm slim mode: Avg. 9 to 10 sec.                                                                  |
| 8  | Fiber Tensile Test Force     |                                                                                                     |
| 9  | Electrode Life               |                                                                                                     |
| 10 | Physical Description         | Dimensions W                                                                                        |
|    |                              | Approx. 170 mm without protection                                                                   |
|    |                              | Dimensions D                                                                                        |
|    |                              | Approx. 173 mm without protection                                                                   |
| 11 | Environmental Condition      | Dimensions H                                                                                        |
|    |                              | Approx. 150 mm without protection                                                                   |
|    |                              | Weight                                                                                              |
|    |                              | Approx. 2.8 kg including battery                                                                    |
| 12 | AC Adaptor                   | Temperature                                                                                         |
|    |                              | Operate: -10 to 50°C                                                                                |
|    |                              | Storage: -40 to 80°C                                                                                |
|    |                              | Humidity                                                                                            |
| 13 | Battery Pack                 | Altitude                                                                                            |
|    |                              | Max. 5,000 m                                                                                        |
|    |                              | Input                                                                                               |
|    |                              | AC100 to 240 V, 50/60 Hz, Max. 1.5 A                                                                |
| 14 | Display                      | Type                                                                                                |
|    |                              | Rechargeable Lithium Ion                                                                            |
|    |                              | Output                                                                                              |
|    |                              | Approx. DC14.4V / 6,380 mAh                                                                         |
| 15 | Illumination                 | Capacity                                                                                            |
|    |                              | Approx. 300 splice and heat cycles                                                                  |
|    |                              | Recharge: 0 to 30°C                                                                                 |
|    |                              | Storage: -20 to 30°C                                                                                |
| 16 | External Led Lamp            | Battery Life                                                                                        |
|    |                              | Approx. 500 recharge cycles                                                                         |
|    |                              | Recharge Time                                                                                       |
|    |                              | Approx. 5-8 hours from empty                                                                        |
|    |                              | LCD Monitor                                                                                         |
|    |                              | TFT 5 inches with touch screen                                                                      |
|    |                              | Magnification                                                                                       |
|    |                              | 200 to 320x                                                                                         |
|    |                              | V-Grooves                                                                                           |
|    |                              | LED Lamp                                                                                            |
|    |                              | USB2.0 Mini B type                                                                                  |
|    |                              | USB2.0 A type, Approx. DC5V, 500 mA                                                                 |



|    |                |                       |                                           |
|----|----------------|-----------------------|-------------------------------------------|
|    | Interface      | Ribbon Stripper       | Mini DIN 6 pin, DC12V, Max. 1A            |
|    |                | Wireless              | Bluetooth 4.1 LE                          |
|    |                | Splice Mode           | 100 splice modes                          |
|    |                | Heat Mode             | 30 heat modes                             |
|    |                | Splice Result         | 20,000 splices                            |
|    |                | Splice Image          | 100 images                                |
| 17 | Data Storage   | Screw Hole for Tripod |                                           |
| 18 |                |                       | 1/4-20 UNC                                |
| 19 | Other Features | Automatic Functions   | Splice mode select by fiber type analysis |
|    |                |                       | Discharge power calibration               |
|    |                |                       | Wind protector: open/close                |
|    |                |                       | Sheath clamp: open                        |
|    |                |                       | Heater lid: open/close                    |
|    |                |                       | Heater clamp: open/close                  |
|    |                |                       | Video and PDF file stored in splicer      |
|    |                |                       | Easy sleeve positioning clamp             |
|    |                |                       | Electrode                                 |
|    |                |                       | Replacable without tool                   |

#### Splicing Machine Package Contents:

- Fusion Splicer Fujikura 90S+ — 1 pc;
- Battery — 1 pc;
- Spare Battery — 2 pc;
- AC Adaptor — 1 pc;
- USB Cable — 1 pc;
- Fusion Splicer Strap — 1 pc;
- Spare Electrodes — 2 set;
- Carrying Case — 1 pc;
- Alcohol Dispenser (AP-02) — 1 pc.
- Single Fiber Stripper — 2 pc;
- Optical Fiber Cleaver — 2 pc;
- Fiber Setting Plate (AD-10-M24) — 1 pc;
- Hexagonal Wrench (HEX-01) — 1 pc;
- With 6 months warranty.





## 5.6 Power Meter (EPM-50 Power Meter):

### Technical Specifications (EXFO):

|                                                              |                   |                                    |                 |
|--------------------------------------------------------------|-------------------|------------------------------------|-----------------|
| Power measurement range—pass zone for continuous data stream | 1310 nm           | 8 to -40 dBm                       | 8 to -40 dBm    |
|                                                              | 1490 nm           | 12 to -40 dBm                      | 12 to -40 dBm   |
|                                                              | 1550 nm           | 25 to -40 dBm                      | N/A             |
| Burst measurement capability                                 | CO to ONT         |                                    |                 |
| Burst measurement range                                      | 1310 nm           | 8 to -30 dBm                       | 8 to -30 dBm    |
| ORL                                                          | 1550 nm           | 55 dB                              | 55 dB           |
| Pass-through insertion loss                                  | 1.5 dB            |                                    |                 |
| Spectral passband                                            | 1310 nm           | 1260 to 1360 nm                    | 1260 to 1360 nm |
|                                                              | 1490 nm           | 1480 to 1500 nm                    | 1480 to 1500 nm |
|                                                              | 1550 nm           | 1539 to 1565 nm                    | 1539 to 1565 nm |
| Power uncertainty                                            | 0.5 dB            |                                    |                 |
| Calibrated wavelengths                                       | 1310/1490/1550 nm |                                    |                 |
| Power measurement range                                      | 1310 nm           | 25 to -40 dBm                      | 25 to -40 dBm   |
|                                                              | 1490 nm           | 25 to -40 dBm                      | 25 to -40 dBm   |
|                                                              | 1550 nm           | 25 to -40 dBm                      | 25 to -40 dBm   |
| General Specifications                                       |                   |                                    |                 |
| Operating                                                    |                   | -10 °C to 50 °C (14 °F to 122 °F)  |                 |
| Storage                                                      |                   | -40 °C to 70 °C (-40 °F to 158 °F) |                 |

- EPM-50 Optical Power Meter – 1 pc;
- USB cable – 1 pc;
- Wrist strap – 1 pc;
- Protective cover for optical ports – 1 pc;
- CD with software and user guide – 1 pc;
- Permanently software;
- With 6 months warranty.



## 5.7 Light Source (ELS-50 Light Source):

### Specifications (EXFO):

- Central Wavelengths (nm): 1310nm (+/- 20nm), 1550nm (+/-20nm);
- Spectral Width (nm): < 5;
- Output Power (dBm): > -5;
- Power Stability (dB): +/-0.10;
- Battery Life (hours): 60;
- Tone Generation (Hz): 270, 1k, 2k;
- Rugged design;
- Excellent power stability for reliable loss measurements;
- Interchangeable connector adapters;
- Up to 60 hours of battery life;



*[Handwritten signature]*

- Tone generation for fiber identification;
- With 6 months warranty.



## 5.8 Optical Time-Domain Reflectometer (OTDR):

FTBx-735C-SM2-OPM2-OI-IPRO ultra-long-haul OTDR :

| TECHNICAL SPECIFICATIONS                            |                                                                        |
|-----------------------------------------------------|------------------------------------------------------------------------|
| Wavelengths (nm) <sup>a</sup>                       | 1310 ± 20/1490 ± 20/1550 ± 20/1625 ± 10                                |
| SM live port built-in filter                        | 1625 nm: highpass >1595 nm<br>isolation >50 dB from 1270 nm to 1585 nm |
| Dynamic range at 20 µs (dB) <sup>b</sup>            | -42/41/41/41                                                           |
| Event dead zone (m) <sup>c</sup>                    | 0.5                                                                    |
| Attenuation dead zone (m) <sup>d</sup>              | 2.5                                                                    |
| Distance range (km)                                 | 0.1 to 400                                                             |
| Pulse width (ns)                                    | 3 to 20 000                                                            |
| Linearity (dB/dB) <sup>a</sup>                      | ±0.03                                                                  |
| PON dead zone (m) <sup>e</sup>                      | 30                                                                     |
| Loss threshold (dB)                                 | 0.01                                                                   |
| Loss resolution (dB)                                | 0.001                                                                  |
| Sampling resolution (m)                             | 0.04 to 10                                                             |
| Sampling points                                     | Up to 256 000                                                          |
| Distance uncertainty (m) <sup>f</sup>               | ±(0.75 + 0.0025 % x distance + sampling resolution)                    |
| Measurement time                                    | User-defined (maximum: 60 minutes)                                     |
| Typical real-time refresh (Hz)                      | 4                                                                      |
| Stable source output power (dBm) <sup>g</sup>       | -2.5                                                                   |
| Reflectance (dB) <sup>a</sup>                       | ±2                                                                     |
| ( IOLM) Software License                            | Permeant                                                               |
| TECHNICAL SPECIFICATIONS (in-line power meter) a, h |                                                                        |
| Input power range (dBm)                             | 1490 nm: -65 to 18<br>1550 or 1577 nm: -50 to 28                       |
| PON power meter (nm)                                | Two channels: 1490/1550                                                |
| Broadband power meter (nm)                          | One channel: 1270 to 1625                                              |






|     |                                                                 |                           |                           |
|-----|-----------------------------------------------------------------|---------------------------|---------------------------|
| 5   | معاینه اجناس                                                    | ✓                         |                           |
| 4   | پیش بردن پرونده مالیه و کمرکی.                                  |                           | ✓                         |
| 3   | انتقال وسائل در کدام شرکت افغان تله کام و لایت کابل معیار قلمه؛ |                           | ✓                         |
| 2   | تهیه نمودن وسائل با کیفیت بهتر مطابق قرارداد؛                   |                           | ✓                         |
| 1   | چک نمودن وسائل مطابق قرارداد و تهیه نمودن گزارش؛                | ✓                         |                           |
| 6.1 | اجناس:                                                          | مسولیت شرکت افغان تله کام | مسولیت شرکت قرارداد کننده |

6 مسولیت های فرمایشی دهنده و فرمایش گیرنده:



|                                                   |                                                                                                                        |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Power uncertainty (dB) "                          | ±0.2                                                                                                                   |
| Calibrated wavelengths (nm)                       | 1310, 1490, 1550 and 1625                                                                                              |
| PON power meter spectral band (nm)                | 1450 to 1530                                                                                                           |
| Broadband power meter spectral band (nm)          | 1270 to 1625                                                                                                           |
| PON power meter selectable wavelengths (nm)       | 1490, 1550, 1490/1550                                                                                                  |
| Broadband power meter selectable wavelengths (nm) | 1270, 1290, 1310, 1330, 1350, 1370, 1390, 1410, 1430, 1450, 1470, 1490, 1510, 1530, 1550, 1570, 1577, 1590, 1610, 1625 |
| Display resolution (dB)                           | 0.1                                                                                                                    |
| PON power meter ORL (dB) "                        | -55                                                                                                                    |
| Broadband power meter ORL (dB) "                  | -50                                                                                                                    |



بعد از عقد قرارداد

ګډام شرکت افغان تلیکام ولایت کابل مهتاب قلعه؛

[illegible]





|    |                                                                                                                                                                                                |      |       |  |  |  |  |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|--|--|--|--|
| 25 | LC/UPC-SC/APC-Duplex-SM-SM-Φ3.0-0.5m based on SoW                                                                                                                                              | pair | 500   |  |  |  |  |
| 26 | LC/UPC-SC/APC-Duplex-SM-SM-Φ3.0-1m based on SoW                                                                                                                                                | pair | 500   |  |  |  |  |
| 27 | LC/UPC-SC/APC-Duplex-SM-SM-Φ3.0-2m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 28 | LC/UPC-SC/APC-Duplex-SM-SM-Φ3.0-3m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 29 | LC/UPC-SC/APC-Duplex-SM-SM-Φ3.0-5m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 30 | LC/UPC-SC/APC-Duplex-SM-SM-Φ3.0-10m based on SoW                                                                                                                                               | pair | 2,000 |  |  |  |  |
| 31 | LC/UPC-LC/UPC-Duplex-SM-SM-Φ3.0-0.5m based on SoW                                                                                                                                              | pair | 2,000 |  |  |  |  |
| 32 | LC/UPC-LC/UPC-Duplex-SM-SM-Φ3.0-1m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 33 | LC/UPC-LC/UPC-Duplex-SM-SM-Φ3.0-2m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 34 | LC/UPC-LC/UPC-Duplex-SM-SM-Φ3.0-3m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 35 | LC/UPC-LC/UPC-Duplex-SM-SM-Φ3.0-5m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 36 | LC/UPC-LC/UPC-Duplex-SM-SM-Φ3.0-10m based on SoW                                                                                                                                               | pair | 2,000 |  |  |  |  |
| 37 | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-0.5m based on SoW                                                                                                                                              | pair | 2,000 |  |  |  |  |
| 38 | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-1m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 39 | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-2m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 40 | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-3m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 41 | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-5m based on SoW                                                                                                                                                | pair | 2,000 |  |  |  |  |
| 42 | LC/UPC-SC/UPC-Duplex-SM-SM-Φ3.0-10m based on SoW                                                                                                                                               | pair | 2,000 |  |  |  |  |
| 43 | Singlemode 1 E2000/APC-SC/PC G.652D 20M Yellow   AE2000-SC-S2-L40//E2000/APC-SC/UPC SM SX 2.0mm 20M//E2000/APC-SC/UPC G.652D 1F Φ3 PVC 20M based on SoW memorandum# 5.4 Technical Requirements | pair | 400   |  |  |  |  |
| 44 | Singlemode 1 E2000/APC-SC/PC G.652D 10M Yellow   AE2000-SC-S2-L40//E2000/APC-SC/UPC SM SX 2.0mm 10M//E2000/APC-SC/UPC G.652D 1F Φ3 PVC10M based on SoW memorandum# 5.4 Technical Requirements  | pair | 400   |  |  |  |  |
| 45 | Splicing Machine 90s+ and tools kits with all accessories based on SoW memorandum# 5.5 Technical Requirements                                                                                  | pcs  | 10    |  |  |  |  |
| 46 | Power Meter based on SoW memorandum# 5.6 Technical Requirements                                                                                                                                | pcs  | 5     |  |  |  |  |
| 47 | Light Source based on SoW memorandum# 5.7 Technical Requirements                                                                                                                               | pcs  | 20    |  |  |  |  |
| 48 | Optical Time-Domain Reflectometer (OTDR) based on SoW memorandum# 5.8 Technical Requirements                                                                                                   | pcs  | 5     |  |  |  |  |

הנה כי כן, ובתנאי שיתא, וסיוע וקדש, ושתאם לנבואה ולסוד ולתורה, ויהי ביום שיתאם חתום (א)

- 7.5: **حیاتیاتی**

• طی و متباین متباین و معیار، جنسی جزیلی از بعد ادراک و مجموعی قیمت 80% متباین

- 7.4:  $\frac{1}{2} \log 2$

[illegible]

- جنتیہ دہلی (پنج) ۵ جولائی ۱۹۱۷ء

- 7.2 جنسی وراثتی اور جنسی وراثت کا اثر

- [illegible]

- L မိမိ၏ ခြားနားမှုကို မိမိတို့အား: